

RKLT22

2X2 LED Troffer Retrofit Kit

Catalog #

Note

Type

Product Description

The RKLT22 LED troffer retrofit kit combines Osram Sylvania LED modules and LED driver, delivers over 3600 lumens at 3500K/4000K/5000K. The RKLT22 LED troffer retrofit kit is 0-10V dimming, accepts 100-277VAC, consumes only 35 watts and produces equivalent luminous intensity as 56W fluorescent fixture.

The kit includes one piece 2'X2' steel plate constructed with LED modules and LED driver, two pieces side bars, and four pieces clips. The kit provides a quick and easy upgrade solution, fits both parabolic and lensed troffer housings.

Performance Summary

Input Voltage: 120/277VAC

Input Power: 35W (56W Fluorescent Fixture Equivalent)

Efficacy: 110 LPW

PF: 0.95

THD: 15%

Lumen Output: 3600 Lumens

CCT: 3500K/4000K/5000K

CRI: 80

R9: 10

L70 Life: 50,000 Hours

Warranty: 5 Years

2'X2' Size

No Ballast or Starter Required

Indoor Application



Ordering Information

Example: RKLT2235HU40K36L10D

MODEL	WATTAGE	VOLTAGE	COLOR TEMP	LUMEN OUTPUT	LIGHTING CONTROL
RKLT22 2'X2' LED Troffer Retrofit Kit	35 35W	HU 100-277VAC	35K 3500K 40K 4000K 50K 5000K	36L 3600lm	10D 0-10V Dimming

Notes:

Lead times will vary depending on options selected. Consult with your sales representative.

Specifications tolerance: ± 5%.

web: www.pozeen.com | e-mail: sales@pozeen.com | phone: (+86) 21-50201276

1588 Lianhang Road, Pudong District, Shanghai 200123, China

Pozeen
QUALITY.VALUE

RKLT22

2X2 LED Troffer Retrofit Kit

Catalog #	
Note	
Type	

Features & Specifications

CONSTRUCTION & MATERIALS

- Two side bars
- One-piece durable steel plate constructed with LED modules and LED driver
- Fit both parabolic and lensed troffer fixtures
- Avoid the removal of the existing fixture from the ceiling cavity and the associated asbestos abatement

MOUNTING AND WIRING

- Drill the supplied tek screws into existing troffer fixture to mount the side bars
- Put the steel plate onto the side bars, turn the clips 90 degrees to lock
- Push the stripped wire conductor into luminaire disconnect

ENVIRONMENTAL SYSTEM

- Indoor and dry location

OPTICAL SYSTEM

- Designed with the look of traditional fluorescent fixtures
- High performance Osram Sylvania LED modules
- Color temperature available in 3500K, 4000K and 5000K
- 50,000 hours life

ELECTRICAL SYSTEM

- Integral high performance Osram Sylvania LED driver
- Universal input voltage 120-277VAC, 50/60Hz

PHYSICAL SPECIFICATION	
Dimension	L23.80 X W23.80 inch
Housing	Sheet steel
ENVIRONMENTAL SPECIFICATION	
Temp Range	-13-113°F operating (-25-45 °C)
Humidity Range	20% - 85% RH
OPTICAL SPECIFICATION	
Lumen Output	3600 lm
Efficacy	110 lm/W
CCT	3500K/4000K/5000K
CRI	80
R9	10
ELECTRICAL SPECIFICATION	
Input Voltage	100-277 VAC, 50/60 Hz
Input Power	35 W
Power Factor	0.95
Total Harmonic Distortion	15%
LONGEVITY AND WARRANTY	
L70 Life	50,000 hrs
Warranty	5 years
LISTING AND CERTIFICATES	
Design Lights Consortium (DLC) (pending)	
Lighting Facts (pending)	
UL and cUL (pending)	
CE and RoHS	

Quick Installation Instruction

1. Turn off power, remove the existing socket plate, place the side bars, and drill the tek screws into existing troffer fixture (Fig. 1)
2. Push stripped wire into luminaire disconnect (Fig. 2)
3. Put the steel plate onto the side bars, turn the clips 90 degrees to lock (Fig. 3)
4. Turn on the power and enjoy your Pozeen LED lighting (Fig. 4)



Fig. 1



Fig. 2



Fig. 3



Fig. 4