

## SLPM20

200W Roadway LED Street Light

Catalog #

Note

Type

### Product Description

The SLPM20 roadway LED street light utilizes CREE LM80 LEDs and Meanwell LED driver to ensure long life and high thermal endurance for the municipality market segment with performance and style that fits into a broad range of outdoor environments. The SLPM20 LED street light accepts 120-277VAC, consumes 200W and delivers 17000 lumens at 5000K.

The SLPM20 fixture is constructed from heavy duty die-cast aluminum housing and high impact IES lens. The luminaire housing is equipped with gasket and provides a dustproof and waterproof operation, and optional with lighting control gears and photo cell sensors. The SLPM20 LED street light is suitable for applications of streets, roadways, pedestrian walkways, bikeways, parking lots, and campuses.

### Performance Summary

120-277VAC Input Voltage

200W Input Power, Equivalent to 500W MH

85 LPW Efficacy

17000 Lumens Light Output

5000K Color Temperature

IES Type II, III, V Distribution Optics

50,000 Hours Lifetime

5 Years Warranty

IP65 Rated for Outdoor Application

Pole Mounting



### Ordering Information

Example: SLPM20HU50K170L20TPC

MODEL	VOLTAGE	COLOR TEMP	LUMEN OUTPUT	OPTICS TYPE	OPTOINS
SLPM20 200W LED Street Light	HU 120-277VAC	50K <sup>1</sup> 5000K	170L 17000LM	20T Type II 30T Type III 50T Type V	PC Photocell

#### Notes:

- 3000K/3500K/4000K available for special order.
- Lead times will vary depending on options selected. Consult with your sales representative.

web: [www.pozeen.com](http://www.pozeen.com) | e-mail: [sales@pozeen.com](mailto:sales@pozeen.com) | phone: (+86) 21-50201276

1588 Lianhang Road, Pudong District, Shanghai 200123, China

# Pozeen

## SLPM20

200W Roadway LED Street Light

Catalog #	
Note	
Type	

### Features & Specifications

#### CONSTRUCTION & MATERIALS

- Die-cast aluminum housing
- Integral secondary heat sink to optimize thermal transfer and maximize performance and life of LED
- Driver is mounted in direct contact with the chamber for a low operating temperature and long life
- Dust and water proof

#### MOUNTING AND WIRING

- Mount directly on street light arm

#### ENVIRONMENTAL SYSTEM

- IP65 rated and suitable for outdoor locations

#### ELECTRICAL SYSTEM

- Integral high performance Mean Well LED driver
- Universal input voltage 120-277VAC, 50/60Hz

#### OPTICAL SYSTEM

- High quality shock proof PMMA lens with UV inhibitors
- IES Type II, III, V optics
- High performance CREE LEDs mounted on metal core board and integral aluminum heat sink
- Color temperature: 5000K. Other color temperature available for special order, consult factory for lead time

#### LIGHTING CONTROL

- Photo cell sensor available for special order, consult factory for lead time

PHYSICAL SPECIFICATION	
Dimension	755X320X126.5 mm
Housing	Die cast aluminum
Lens Type	High quality shock proof PMMA lens
Finish	Silver
Mounting	Pole mount
ENVIRONMENTAL SPECIFICATION	
Temp Range	-30-130 °F operating -40-140 °F storage
Humidity Range	20% - 85% RH
Ingress Protection	IP65
ELECTRICAL SPECIFICATION	
Input Voltage	120-277 VAC, 50/60 Hz
Input Power	200 W
Power Factor	0.9
Total Harmonic Distortion	15%
OPTICAL SPECIFICATION	
Luminous Flux	17000 lm
Efficacy	85 lm/W
CCT	5000 K
CRI	80
Optics	Type II, III, V
LIGHTING CONTROL	
Photo Cell	Optional
LONGEVITY AND WARRANTY	
L70 Life	50,000 hrs
Warranty	5 years
LISTING AND CERTIFICATES	
UL, cUL	
CE and RoHS	