

WPFC60

60W Full Cutoff LED Wall Pack

Catalog #

Note

Type

Product Description

The WPFC60 full cutoff LED wall pack delivers 5600 lumens at 5500K. The WPFC60 LED wall pack accepts 120-277VAC, consumes 57 watts and produces luminous intensity equivalent to 250W metal halide. The WPFC60 LED wall pack is a perfect replacement for traditional outdoor wall packs.

Performance Summary

120-277VAC Input Voltage

57W Input Power, 250W Metal Halide Equivalent

98 LPW Efficacy

5600 Lumens Lighting Output

5500K Color Temperature

80 CRI

94,000 Hours L70 Lifetime

5 Years Warranty

IP65 Rated for Outdoor Application

Recessed Outlet Box or Wall Surface Mounting



DESIGNLIGHTS
CONSORTIUM



Ordering Information

Example: WPFC60HU55K56L

MODEL	WATTAGE	VOLTAGE	COLOR TEMP	LUMEN OUTPUT	LIGHTING CONTROL	OPTIONS
WPFC Full Cutoff LED Wall Pack	60 57W	HU 120-277VAC	55K 5500K	56L 5600LM	(blank) Static	(blank) Black Finish

Notes:

3500K/4000K/5000K available for special order. Consult with your sales representative for lead time.

WPFC60

60W Full Cutoff LED Wall Pack

Catalog #	
Note	
Type	

Features & Specifications

CONSTRUCTION & MATERIALS

- Heavy duty die-cast aluminum housing and door, fully gasket sealed to be dirt and bug proof
- Tempered, impact-resistant, clear glass lens
- Integral secondary heat sink to optimize thermal transfer and maximize performance and life of LED
- Driver is mounted in direct contact with the casting for a low operating temperature and long life
- Polyester powder-coated finish, rust and corrosion proof; stabilized to extreme climate changes without cracking or peeling

MOUNTING AND WIRING

- Mount directly over a standard outlet box or for surface wiring via any of the 3 convenient 3/4 inch threaded conduit entry hubs.

ENVIRONMENTAL SYSTEM

- IP65 rated and suitable for wet locations

OPTICAL SYSTEM

- High quality tempered clear glass lens
- Forward throw lighting distribution for area lighting
- High performance SMD LEDs
- Color temperature: 5000K. Other color temperature available for special order, consult factory for lead time.

ELECTRICAL SYSTEM

- Integral high performance LED driver
- Universal input voltage 120-277VAC, 50/60Hz

PHYSICAL SPECIFICATION	
Dimension	18.23X13.78X9.05 inch
Housing	Die cast aluminum
Lens Type	Tempered, impact-resistant, clear glass lens
Finish	Black
Mounting	Recessed outlet box OR wall surface
ENVIRONMENTAL SPECIFICATION	
Temp Range	-30~130 °F operating -40~140 °F storage
Humidity Range	20% - 85% RH
Ingress Protection	IP65
OPTICAL SPECIFICATION	
Luminous Flux	5600 lm
Efficacy	98 lm/W
CCT	5500 K
CRI	80
ELECTRICAL SPECIFICATION	
Input Voltage	120-277 VAC, 50/60 Hz
Input Power	57 W
Power Factor	>0.9
Total Harmonic Distortion	<11%
LONGEVITY AND WARRANTY	
L70 Life	94,000 hrs
Warranty	5 years
LISTING AND CERTIFICATES	
Design Lights Consortium (DLC)	
Lighting Design Lab (LDL)	
Lighting Facts	
ETL and cETL	
CE and RoHS	