

WPSL35

35W Slim LED Wall Pack

Catalog #

Note

Type

Product Description

The WPSL35 slim LED wall pack integrates super-bright LED technology while taking advantage of a stylish, slim profile and rugged die-cast aluminum design.

The WPSL35 accepts 120-277VAC, consumes 35W and produces light intensity equivalent to 175W MH fixture; and is ideal for both commercial and residential applications with wall mounting such as factories, warehouses, self-storage, commercial buildings, entrances, walkways and loading.

Performance Summary

Input voltage: 120-277VAC, 50/60Hz

Input wattage: 35 watts (175W MH fixture equivalent)

Efficacy: 85 LPW

Lumen output: 3100 lumens

CCT: 5000K

CRI: 70 min.

L70 life: 50,000 hours

Warranty: 5 years



Ordering Information

Example: WPSL35HU50K

FAMILY		WATTAGE		VOLTAGE		CCT		OPTIONS	
WPSL	Slim LED Wall Pack	35	35W	HU	120-277VAC	50K	5000K	(blank)	Bronze Finish

Note

1. Other color temperature available for special order.
2. Lead times will vary depending on options selected. Consult with your sales representative.

WPSL35

35W Slim LED Wall Pack

Catalog #	
Note	
Type	

Features & Specifications

CONSTRUCTION & MATERIALS

- Stylish and slim profile design
- Die-cast aluminum housing with rubber gasket on back plate
- Dark bronze finish

MOUNTING AND WIRING

- Wall mounting: direct junction box mounting

ENVIRONMENTAL SYSTEM

- Suitable for wet location
- Operating temperature range: -4°F-104°F (-20-40°C)

ELECTRICAL SYSTEM

- High performance LED driver
- Universal input voltage 120-277VAC, 50/60Hz

OPTICAL SYSTEM

- Tempered, impact-resistant, clear glass lens
- Custom-engineered, mirrored anodized reflector
- Forward throw lighting distribution for area lighting
- High performance LM80 LEDs
- Color temperature: 5000K. Other color temperature available for special order, consult factory for lead time
- Minimum 50,000 hours life

LIGHTING CONTROL

- Available for special order, consult factory for lead time

PHYSICAL SPECIFICATION	
Length	9.45" (240mm)
Width	8.07" (205mm)
Height	3.74" (95mm)
Net weight	5.07 lb (2.30 kg)
Housing material	Die-cast aluminum
Finish	Bronze
MOUNTING AND WIRING	
Mounting	Wall mount
ENVIRONMENTAL SPECIFICATION	
Operating temp.	-4°F-104°F (-20-40°C)
Ingress protection	Suitable for wet location
ELECTRICAL SPECIFICATION	
Input voltage	120-277VAC, 50/60Hz
Input wattage	35W
Equivalent wattage	175W MH
Power factor	0.90 min.
Total harmonic distortion	20% max.
OPTICAL SPECIFICATION	
Luminous flux	3100 lm
Efficacy	85 lm/W
CCT	5000K
CRI	70 min.
Lens	Tempered clear glass
LIGHTING CONTROL	
Dimming capacity	Optional
LONGEVITY AND WARRANTY	
L70 life	50,000 hrs.
Warranty	5 years
LISTING AND CERTIFICATES	
ETL, cETL	
FCC	
CE, RoHS	